

SAKRAL STRAIGHT CUT ROUNDED CORNER

- Eye-catching peak and trough structure
- Robust appearance thanks to the impressive thickness of its material
- If requested, the surface can be roughened to aid the rapid development of a natural patina
- Especially suitable for old church roofs, castles and palaces
- Natural, timeless and dignified beauty
- Configure roofs to suit your needs, thanks to the wide range of cut shapes

TECHNICAL DATA

Size (appr.)	180 x 380 x 18 mm
Max. coverage width (approx.)	180 mm
Min. gauge (approx.)	145 mm
Covering length on av. approx.	155 mm
Max. gauge (approx.)	165 mm
Average tile requirement (approx.)	36 pcs/m ²
Unit weight (approx.)	2.6 kg/piece
Weight per m ² (approx.)	93.6 kg/m ²
Weight per pallet (approx.)	1141 kg
Pcs per mini-pack	6 piece
Pcs per pallet	360 piece



APPLICATIONS

ADDITIONAL MEASURES ACCORDING TO CREATON MANUFACTURER'S SPECIFICATIONS	
Standard roof pitch CREATON DE in combination with additional measures according to manufacturer's specifications	24 °
Installation of a trussing sheet/glued sub-roof without nail seals, possible CREATON products: DUO extra, DUO longlife ND extra, TRIO extra, QUATTRO longlife extra	≥ 24 °
Installation of a trussing sheet/glued sub-roof without nail seals, possible CREATON products: DUO longlife ND extra	≥ 22 °
Installation of a trussing sheet/glued sub-roof with nail seals, possible CREATON products: DUO extra, DUO longlife ND extra, TRIO extra, QUATTRO longlife extra	≥ 22 °
Installation as a rainproof sub-roof, possible CREATON products: DUO longlife ND extra, TRIO extra, QUATTRO longlife extra	≥ 18 °
Installation as a watertight sub-roof, possible CREATON products: QUATTRO longlife extra	≥ 10 °
Installation as a watertight sub-roof welded in a 7° special solution, please observe separate installation guidelines, possible CREATON products: QUATTRO longlife extra	-

TECHNICAL INFORMATION

- Please consider the sample letter for the standard CREATON roof pitches.

